

MAINTENANCE

MAINTENANCE SCHEDULE

Perform the Pre-ride inspection in the Owner's Manual at each scheduled maintenance period.

I: Inspect and clean, adjust, lubricate or replace if necessary. C: Clean. R: Replace. A: Adjust. L: Lubricate.

The following items require some mechanical knowledge. Certain items (particularly those marked * and **) may require more technical information and tools. Consult your Honda dealer.

ITEMS	FREQUENCY	WHICHEVER COMES FIRST ⇩	ODOMETER READING (NOTE 1)								REFER TO PAGE	
			⇨	0.6	4	8	12	16	20	24		
			X1,000 mi X1,000 km	1.0	6.4	12.8	19.2	25.6	32.0	38.4		
EMISSION RELATED ITEMS	* FUEL LINE				I			I		I	4-5	
	* THROTTLE OPERATION				I			I		I	4-5	
	* CHOKE OPERATION				I			I		I	4-6	
	AIR CLEANER	NOTE 2					R			R	4-7	
	* SUB AIR CLEANER					R				R	4-8	
	CRANKCASE BREATHER	NOTE 3			C	C	C	C	C	C	4-8	
	SPARK PLUG				I	R	I	R	I	R	4-9	
	* VALVE CLEARANCE				I		I		I		4-10	
	ENGINE OIL			INITIAL = 600 mi (1,000 km) or 1 month : R REGULAR = Every 8,000 mi (12,800 km) or 12 months : R								4-12
	ENGINE OIL FILTER				R		R		R		R	4-13
	* ENGINE IDLE SPEED				I	I	I	I	I	I	I	4-15
	RADIATOR COOLANT	NOTE 4					I		I		R	4-15
* COOLING SYSTEM						I		I		I	4-15	
* SECONDARY AIR SUPPLY SYSTEM						I		I		I	4-16	
* EVAP CONTROL SYSTEM	NOTE 5					I				I	4-17	
NON-EMISSION RELATED ITEMS	FINAL DRIVE OIL					I		I		R	4-18	
	BRAKE FLUID	NOTE 4				I	I	R	I	I	R	4-19
	BRAKE SHOES/PADS WEAR					I	I	I	I	I	4-20	
	BRAKE SYSTEM					I		I		I	4-20	
	* BRAKE LIGHT SWITCH					I		I		I	4-22	
	* HEADLIGHT AIM					I		I		I	4-22	
	CLUTCH SYSTEM					I	I	I	I	I	4-22	
	SIDESTAND					I		I		I	4-23	
	* SUSPENSION					I		I		I	4-24	
	* NUTS, BOLTS, FASTENERS					I		I		I	4-24	
** WHEELS/TIRES					I	I	I	I	I	4-25		
** STEERING HEAD BEARINGS					I		I		I	4-26		

* Should be serviced by your dealer, unless the owner has proper tools and service data and is mechanically qualified

** In the interest of safety, we recommend these items be serviced only by your Honda dealer

NOTES:

- At higher odometer reading, repeat at the frequency interval established here.
- Service more frequently when riding in unusually wet or dusty areas.
- Service more frequently when riding in rain or at full throttle.
- Replace every 2 years, or at indicated odometer interval, whichever comes first. Replacement requires mechanical skill.
- California type only.